Schindler 3300 AP MMR Planning Data (EN81)

Capacity GQ kg	**Passengers** max. Per.	**Speed** VKN m/s	**Travel height** max. HQ m	**Number of stops** max. ZE	**Car** BK mm	TK mm	HK mm	**Door** BT mm	HT mm	**Shaft** BS mm	TS mm	HSK mm	HSG mm
630	8	1.00	45	15	1400	1100	2350	800	2100	1875	1450	3650	1100
					1400	1100	2500	800	2100	1875	1450	3800	
					1250	1250	2350	800	2100	1800	1600	3650	
					1250	1250	2500	800	2100	1800	1600	3800	
					1100	1400	2350	800	2100	1800	1750	3650	
					1100	1400	2500	800	2100	1800	1750	3800	
		1.50	60	20	1400	1100	2350	800	2100	1875	1450	3800	1200
					1400	1100	2500	800	2100	1875	1450	3950	
					1250	1250	2350	800	2100	1800	1600	3800	
					1250	1250	2500	800	2100	1800	1600	3950	
					1100	1400	2350	800	2100	1800	1750	3800	
					1100	1400	2500	800	2100	1800	1750	3950	
		1.75	60	20	1400	1100	2350	800	2100	1875	1450	3850	1250
					1400	1100	2500	800	2100	1875	1450	4000	
					1250	1250	2350	800	2100	1800	1600	3850	
					1250	1250	2500	800	2100	1800	1600	4000	
					1100	1400	2350	800	2100	1800	1750	3850	
					1100	1400	2500	800	2100	1800	1750	4000	
800	10	1.00	45	15	1400	1350	2350	800	2100	1875	1700	3650	1100
					1400	1350	2500	800	2100	1875	1700	3800	
					1350	1400	2350	800	2100	1850	1750	3650	
					1350	1400	2350	900	2100	2000	1750	3650	
					1350	1400	2500	800	2100	1850	1750	3800	
					1350	1400	2500	900	2100	2000	1750	3800	
		1.50	60	20	1400	1350	2350	800	2100	1875	1700	3800	1200
					1400	1350	2500	800	2100	1875	1700	3950	
					1350	1400	2350	800	2100	1850	1750	3800	
					1350	1400	2350	900	2100	2000	1750	3800	
					1350	1400	2500	800	2100	1850	1750	3950	
					1350	1400	2500	900	2100	2000	1750	3950	
		1.75	60	20	1400	1350	2350	800	2100	1875	1700	3850	1250
					1400	1350	2500	800	2100	1875	1700	4000	
					1350	1400	2350	800	2100	1850	1750	3850	
					1350	1400	2350	900	2100	2000	1750	3850	
					1350	1400	2500	800	2100	1850	1750	4000	
					1350	1400	2500	900	2100	2000	1750	4000	

GQ Capacity
VKN Speed
HQ Travel height
ZE Stops

BK Car width
TK Car depth
HK Car height

BT Door width
HT Door height

BS Shaft width
TS Shaft depth

HSK Headroom height
HSG Pit depth

Remarks:
– Our equipment is designed to withstand a temperature range of 5 to 40°C
– To achieve a suitable temperature for service personnel, the shaft temperature should be kept within the range of 5 to 35°C
– The humidity in the shaft should not exceed 90% in monthly average and 95% in daily average without condensation
– Table of dimensions as per EN81, for other country codes and specific requirements, please contact our local sales office
– Shaft dimensions width & depth are based on clear dimension +/-25mm horizontal tolerances over the total shaft height
– All given information is for general reference and planning. For specific construction detail, please contact our local sales office

Schindler 3300 AP MMR Planning Data (EN81)

Capacity	Passengers max.	Speed	Travel height max.	Number of stops max.	Car			Door		Shaft			
GQ kg	Per.	VKN m/s	HQ m	ZE	BK mm	TK mm	HK mm	BT mm	HT mm	BS mm	TS mm	HSK mm	HSG mm
1000	13	1.00	45	15	1100	2100	2350	800	2100	1800	2450	3650	1100
					1100	2100	2350	900	2100	2000	2450	3650	
					1100	2100	2500	800	2100	1800	2450	3800	
					1100	2100	2500	900	2100	2000	2450	3800	
					1600	1500	2350	900	2100	2075	1850	3650	
					1600	1500	2500	900	2100	2075	1850	3800	
					1600	1400	2350	900	2100	2075	1750	3650	
					1600	1400	2350	1000	2100	2200	1750	3650	
					1600	1400	2500	900	2100	2075	1750	3800	
					1600	1400	2500	1000	2100	2200	1750	3800	
		1.50	60	20	1100	2100	2350	800	2100	1800	2450	3800	1200
					1100	2100	2350	900	2100	2000	2450	3800	
					1100	2100	2500	800	2100	1800	2450	3950	
					1100	2100	2500	900	2100	2000	2450	3950	
					1600	1500	2350	900	2100	2075	1850	3800	
					1600	1500	2500	900	2100	2075	1850	3950	
					1600	1400	2350	900	2100	2075	1750	3800	
					1600	1400	2350	1000	2100	2200	1750	3800	
					1600	1400	2500	900	2100	2075	1750	3950	
					1600	1400	2500	1000	2100	2200	1750	3950	
		1.75	60	20	1100	2100	2350	800	2100	1800	2450	3850	1250
					1100	2100	2350	900	2100	2000	2450	3850	
					1100	2100	2500	800	2100	1800	2450	4000	
					1100	2100	2500	900	2100	2000	2450	4000	
					1600	1500	2350	900	2100	2075	1850	3850	
					1600	1500	2500	900	2100	2075	1850	4000	
					1600	1400	2350	900	2100	2075	1750	3850	
					1600	1400	2350	1000	2100	2200	1750	3850	
					1600	1400	2500	900	2100	2075	1750	4000	
					1600	1400	2500	1000	2100	2200	1750	4000	
1150	15	1.00	45	15	1800	1500	2350	1000	2100	2275	1850	3650	1100
					1800	1500	2500	1000	2100	2275	1850	3800	
		1.50	60	20	1800	1500	2350	1000	2100	2275	1850	3800	1200
					1800	1500	2500	1000	2100	2275	1850	3950	
		1.75	60	20	1800	1500	2350	1000	2100	2275	1850	3850	1250
					1800	1500	2500	1000	2100	2275	1850	4000	

GQ Capacity
VKN Speed
HQ Travel height
ZE Stops

BK Car width
TK Car depth
HK Car height

BT Door width
HT Door height

BS Shaft width
TS Shaft depth

HSK Headroom height
HSG Pit depth

Remarks:
– Our equipment is designed to withstand a temperature range of 5 to 40°C
– To achieve a suitable temperature for service personnel, the shaft temperature should be kept within the range of 5 to 35°C
– The humidity in the shaft should not exceed 90% in monthly average and 95% in daily average without condensation
– Table of dimensions as per EN81, for other country codes and specific requirements, please contact our local sales office
– Shaft dimensions width & depth are based on clear dimension +/-25mm horizontal tolerances over the total shaft height
– All given information is for general reference and planning. For specific construction detail, please contact our local sales office