Schindler 3300 AP MRL Planning Data (Malaysia)

Capacity	Passengers max.	Speed	Travel height max.	Number of stops max.	Car			Door		Shaft			
GQ kg	Per.	VKN m/s	HQ m	ZE	BK mm	TK mm	HK mm	BT mm	HT mm	BS mm	TS mm	HSK mm	HSG mm
630	9	1.00	45	15	1400	1100	2350	800	2100	1875	1450	4100	1450
					1400	1100	2500	800	2100	1875	1450	4250	
					1250	1250	2350	800	2100	1800	1600	4100	
					1250	1250	2500	800	2100	1800	1600	4250	
					1100	1400	2350	800	2100	1800	1750	4100	
					1100	1400	2500	800	2100	1800	1750	4250	
		1.50	60	20	1400	1100	2350	800	2100	1875	1450	4100	1400
					1400	1100	2500	800	2100	1875	1450	4250	
					1250	1250	2350	800	2100	1800	1600	4100	
					1250	1250	2500	800	2100	1800	1600	4250	
					1100	1400	2350	800	2100	1800	1750	4100	
					1100	1400	2500	800	2100	1800	1750	4250	
		1.75	60	20	1400	1100	2350	800	2100	1875	1450	4150	1450
					1400	1100	2500	800	2100	1875	1450	4300	
					1250	1250	2350	800	2100	1800	1600	4150	
					1250	1250	2500	800	2100	1800	1600	4300	
					1100	1400	2350	800	2100	1800	1750	4150	
					1100	1400	2500	800	2100	1800	1750	4300	
800	11	1.00	45	15	1400	1350	2350	800	2100	1875	1700	4100	1450
					1400	1350	2500	800	2100	1875	1700	4250	
					1350	1400	2350	800	2100	1850	1750	4100	
					1350	1400	2350	900	2100	2000	1750	4100	
					1350	1400	2500	800	2100	1850	1750	4250	
					1350	1400	2500	900	2100	2000	1750	4250	
		1.50	60	20	1400	1350	2350	800	2100	1875	1700	4100	1400
					1400	1350	2500	800	2100	1875	1700	4250	
					1350	1400	2350	800	2100	1850	1750	4100	
					1350	1400	2350	900	2100	2000	1750	4100	
					1350	1400	2500	800	2100	1850	1750	4250	
					1350	1400	2500	900	2100	2000	1750	4250	
		1.75	60	20	1400	1350	2350	800	2100	1875	1700	4150	1450
					1400	1350	2500	800	2100	1875	1700	4300	
					1350	1400	2350	800	2100	1850	1750	4150	
					1350	1400	2350	900	2100	2000	1750	4150	
					1350	1400	2500	800	2100	1850	1750	4300	
					1350	1400	2500	900	2100	2000	1750	4300	

GQ Capacity
VKN Speed
HQ Travel height
ZE Stops

BK Car width
TK Car depth
HK Car height

BT Door width
HT Door height

BS Shaft width
TS Shaft depth

HSK Headroom height
HSG Pit depth

Remarks:
– Our equipment is designed to withstand a temperature range of 5 to 40°C
– To achieve a suitable temperature for service personnel, the shaft temperature should be kept within the range of 5 to 35°C
– The humidity in the shaft should not exceed 90% in monthly average and 95% in daily average without condensation
– Table of dimensions as per EN81, for other country codes and specific requirements, please contact our local sales office
– Shaft dimensions width & depth are based on clear dimension +/-25mm horizontal tolerances over the total shaft height
– All given information is for general reference and planning. For specific construction detail, please contact our local sales office

Schindler 3300 AP MRL Planning Data (Malaysia)

Capacity	Passengers max.	Speed	Travel height max.	Number of stops max.	Car			Door		Shaft			
GQ kg	Per.	VKN m/s	HQ m	ZE	BK mm	TK mm	HK mm	BT mm	HT mm	BS mm	TS mm	HSK mm	HSG mm
1000	14	1.00	45	15	1100	2100	2350	800	2100	1800	2450	4100	1450
					1100	2100	2350	900	2100	2000	2450	4100	
					1100	2100	2500	800	2100	1800	2450	4250	
					1100	2100	2500	900	2100	2000	2450	4250	
					1600	1500	2350	900	2100	2075	1850	4100	
					1600	1500	2500	900	2100	2075	1850	4250	
					1600	1400	2350	900	2100	2075	1750	4100	
					1600	1400	2350	1000	2100	2200	1750	4100	
					1600	1400	2500	900	2100	2075	1750	4250	
					1600	1400	2500	1000	2100	2200	1750	4250	
		1.50	60	20	1100	2100	2350	800	2100	1800	2450	4100	1400
					1100	2100	2350	900	2100	2000	2450	4100	
					1100	2100	2500	800	2100	1800	2450	4250	
					1100	2100	2500	900	2100	2000	2450	4250	
					1600	1500	2350	900	2100	2075	1850	4100	
					1600	1500	2500	900	2100	2075	1850	4250	
					1600	1400	2350	900	2100	2075	1750	4100	
					1600	1400	2350	1000	2100	2200	1750	4100	
					1600	1400	2500	900	2100	2075	1750	4250	
					1600	1400	2500	1000	2100	2200	1750	4250	
		1.75	60	20	1100	2100	2350	800	2100	1800	2450	4150	1450
					1100	2100	2350	900	2100	2000	2450	4150	
					1100	2100	2500	800	2100	1800	2450	4300	
					1100	2100	2500	900	2100	2000	2450	4300	
					1600	1500	2350	900	2100	2075	1850	4150	
					1600	1500	2500	900	2100	2075	1850	4300	
					1600	1400	2350	900	2100	2075	1750	4150	
					1600	1400	2350	1000	2100	2200	1750	4150	
					1600	1400	2500	900	2100	2075	1750	4300	
					1600	1400	2500	1000	2100	2200	1750	4300	
1150	17	1.00	45	15	1800	1500	2350	1000	2100	2275	1850	4100	1450
					1800	1500	2500	1000	2100	2275	1850	4250	
		1.50	60	20	1800	1500	2350	1000	2100	2275	1850	4100	1400
					1800	1500	2500	1000	2100	2275	1850	4250	
		1.75	60	20	1800	1500	2350	1000	2100	2275	1850	4150	1450
					1800	1500	2500	1000	2100	2275	1850	4300	

GQ Capacity
VKN Speed
HQ Travel height
ZE Stops

BK Car width
TK Car depth
HK Car height

BT Door width
HT Door height

BS Shaft width
TS Shaft depth

HSK Headroom height
HSG Pit depth

Remarks:
– Our equipment is designed to withstand a temperature range of 5 to 40°C
– To achieve a suitable temperature for service personnel, the shaft temperature should be kept within the range of 5 to 35°C
– The humidity in the shaft should not exceed 90% in monthly average and 95% in daily average without condensation
– Table of dimensions as per EN81, for other country codes and specific requirements, please contact our local sales office
– Shaft dimensions width & depth are based on clear dimension +/-25mm horizontal tolerances over the total shaft height
– All given information is for general reference and planning. For specific construction detail, please contact our local sales office